

# Eve P-100 WW

## Highlights

- High output warm white (3500 K) wash light designed for mobile and installation applications
- Included interchangeable magnetic lenses alter the beam to desired angles
- Built-in gel frame holder and 6¼-inch accessory slot to hold barn doors
- Fanless design ensures 100% silent operation
- Flicker-free on video due to the high-frequency LED dimming
- D-Fi USB compatibility for wireless master/slave or DMX control
- Cast aluminum housing provides extra strength without the weight
- powerCON®-compatible power input/output connections for power linking
- Fits best in the CHS-40 VIP gear bag



## Specifications

- DMX Channels: 1, 2 or 4
- DMX Connectors: 3- and 5-pin XLR
- Accessory Holder/Gel Frame Size: 6.25 in (158.75 mm)
- Light Source: 1 COB (warm white) 100 W, (2.7 A), 50,000 hours life expectancy.
- Strobe Rate: 0 to 25 Hz
- Beam Angle: 25°, 35°, or 45°
- Field Angle: 45°, 55°, or 65°
- Illuminance (25°): 7,470 lux @ 2 m
- Illuminance (35°): 1,547 lux @ 2 m (no lens installed)
- Illuminance (45°): 1,469 lux @ 2 m
- Illuminance (25°): 1,085 lux @ 5 m
- Illuminance (35°): 291 lux @ 5 m (no lens installed)
- Illuminance (45°): 214 lux @ 5 m
- Color Temperature: 3500 K
- Power Linking: 14 units @ 120 V; 7 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 122 W, 1.2 A 120 V, 60 Hz
- Power and Current: 119 W, 0.5 A @ 230 V, 50 Hz

- Weight: 7.6 lb (3.5 kg)
- Size: 8.6 x 9.65 x 12 in (220 x 245 x 305 mm)

