

EVE P-140 VW

Highlights

- Variable-white (2700 to 13000 K) wash light designed for mobile and installation applications
- Included interchangeable magnetic lenses alter the beam to desired angles
- Built-in gel frame holder and 6¼-inch accessory slot to hold barn doors
- powerCON®-compatible power input/output connections for power linking
- Fanless design ensures 100% silent operation
- Flexible control options with onboard 3- and 5-pin DMX connectors
- Flicker-free on video due to the high-frequency LED dimming
- D-Fi USB compatibility for wireless master/slave or DMX control
- Cast aluminum housing provides extra strength without the weight
- Fits best in the CHS-40 VIP gear bag



- **Weight: 7.6 lbs. (3.5 kg)**
- **Size: 8.6 x 9.65 x 12 in (220 x 245 x 305 mm)**

Specifications

- DMX Channels: 3 or 9
- DMX Connectors: 3- and 5-pin XLR
- Accessory Holder/Gel Frame Size: 6.25 in (159 mm)
- Light Source: 40 LEDs (13 cool white, 13 warm white, 14 amber)
140 W total, (2.4 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 34 Hz
- Beam Angles: 25°, 35° or 45°
- Field Angles: 45°, 55° or 65°
- Illuminance (25°): 2,490 lux @ 2 m
- Illuminance (35°): 1,245 lux @ 2 m [no lens installed]
- Illuminance (45°): 806 lux @ 2 m
- Illuminance (25°): 590 lux @ 5 m
- Illuminance (35°): 291 lux @ 5 m (no lens installed)
- Illuminance (45°): 189 lux @ 5 m
- Color Temperature Range: 2700 to 13000 K
- Power Linking: 8 units @ 120 V; 16 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 122 W, 1.2 A @ 120 V, 60 Hz
- Power and Current: 111 W, 0.5 A @ 230 V, 50 Hz
- Optional Controllers: DFI USB
- Approvals: CE, MET

